


EASYLOCK PANELS

EASYLOCK PANELS
3343 PEACHTREE RD NE
STE 145-914
ATLANTA, GA 30326
PHONE: (405) 503-2680
www.easylockpanels.com



SPECIFICATIONS

MATERIAL: RECYCLABLE HDPE

UV STABILIZATION: LIMITED

SHAPE: HEXAGONAL CELL STRUCTURE

ANTI-SLIP SYSTEM: MIN. 571 ANTI-SLIP TRIANGLES PER PANEL


LOCKING SYSTEM: CLICKING SYSTEM

WEIGHT: 4.5 LBS PER PANEL; 0.93 LBS PER SQ. FT

* MATERIALS AND ADDITIONAL WATERPROOFING MUST BE RECOMMENDED BY A QUALIFIED ENGINEER

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING. ALL DIMENSIONS ARE APPROX. AND SUBJECT TO NORMAL CONSTRUCTION VARIANCES AND TOLERANCES.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5515-005.



EASYLOCK BASE PANELS

COMPACTED SOIL